

Technical sheet :

# ***TMM 25 4W ST5***


---



 **MANITOU**  
HANDLING YOUR WORLD

|       | Technical characteristics                               |           | Metric                               |
|-------|---|-----------|--------------------------------------|
| 1.1   | Manufacturer  |           | MANITOU                              |
| 1.2   | Model Name  |           | TMM 25 4W ST5                        |
| 1.2.1 | Reach out equipment                                     |           | Pantograph                           |
| 1.3   | Power source  |           | Diesel                               |
| 1.4   | Operator type   |           | Sitting                              |
| 1.5   | Max. capacity   | Q         | 2500 kg                              |
| 1.6   | Load centre of gravity                                  | c         | 500 mm                               |
| 1.8   | Load distance, centre of drive axle to fork             | x         | 500 mm                               |
| 1.9   | Wheelbase   | y         | 1598 mm                              |
|       | Weight  |           |                                      |
| 2.1   | Service weight  |           | 2500 kg                              |
| 2.2   | Weight on front axle (laden) / rear axle (laden)        |           | 3715 kg / 1285 kg                    |
| 2.3   | Weight on front axle (Unladen) / rear axle (Unladen)    |           | 1215 kg / 1285 kg                    |
|       | Wheels  |           |                                      |
| 3.1   | Tyres type  |           | Pneumatic                            |
| 3.2   | Dimensions of front wheels                              |           | 27X10-12 IC30                        |
| 3.3   | Dimensions of rear wheels                               |           | 27X10-12 IC30                        |
| 3.5   | Number of front wheels / rear wheels                    |           | 2 / 1                                |
| 3.5.2 | Drive wheels (front / rear)                             |           | 2 / 1                                |
| 3.6   | Front wheel gauge                                       | b10       | 2143 mm                              |
|       | Dimensions  |           |                                      |
| 4.7   | Height of overhead guard (cabin)                        | h6        | 2120 mm                              |
| 4.8   | Seat height/stand height                                | h7        | 1070 mm                              |
| 4.19  | Overall length  | l1        | 2638 mm                              |
| 4.21  | Overall width   | b1        | 2398 mm                              |
| 4.22  | Forks section / width / length                          | s / e / l | 40 mm x 122 mm / 1200 mm             |
| 4.23  | Fork carriage ISO 2328 (class/form) A/B                 |           | 2A                                   |
| 4.24  | Fork carriage width                                     | b3        | 1260 mm                              |
| 4.25  | Distance between support arms                           | b5        | 1165 mm                              |
| 4.26  | Distance between wheel arms/loading surfaces            | b4        | 1492 mm                              |
| 4.28  | Maximum horizontal extension at COG 600                 | l4        | 1000 mm                              |
| 4.28  | Max. outreach   |           | 1005 mm                              |
| 4.32  | Ground clearance at centre of wheelbase                 | m2        | 272 mm                               |
| 4.37  | Overall length (without forks)                          | l7        | 1438 mm                              |
| 4.38  | Length across wheel arms (4W position)                  | l8        | 2320 mm                              |
| 4.34  | Aisle width for 800 x 1200 pallet lengthways            | Ast       | 3363 mm                              |
| 4.35  | Turning radius  | Wa        | 2463 mm                              |
| 4.36  | Internal turning radius (over tyres)                    | b13       | 672 mm                               |
|       | Performances  |           |                                      |
| 5.1   | Travel speed (laden / unladen)                          |           | 10.60 km/h / 10.70 km/h              |
| 5.2   | Lifting speed (laden / unladen)                         |           | 0.26 m/s / 0.24 m/s                  |
| 5.3   | Lowering speed (laden / unladen)                        |           | 0.38 m/s / 0.24 m/s                  |
| 5.7   | Gradeability (laden / unladen)                          |           | 47 % / 48 %                          |
| 5.10  | Service brake   |           | Hydraulic brakes by loss of pressure |
| 5.9   | Acceleration time (laden / unladen)                     |           | 4.10 s / 2.60 s                      |
| 5.11  | Transmission type                                       |           | Hydrostatic                          |
|       | Engine  |           |                                      |
| 7.1   | Engine brand / nom                                      |           | Kubota - Stage V                     |
| 7.2   | Engine power according to ISO 1585                      |           | 18.50 kW                             |
| 7.3   | Rated speed   |           | 3000 rpm                             |
| 7.4   | Number of cylinders / Capacity of cylinders             |           | 3 - 1123 cm³                         |
| 8.1   | Type of drive control                                   |           | Cable                                |
|       | Miscellaneous   |           |                                      |
| 8.2   | Working hydraulic pressure for attachments              |           | 190 bar                              |
| 8.3   | Oil flow rate for attachments                           |           | 43 l/min                             |
| 8.4   | Sound level at the driver's ear according to DIN 12 053 |           | 84 dB                                |

## TMM 25 4W ST5 - Dimensional drawing



## Characteristics of masts and residual capacities

| Residual Capacity (Maximum Height & LC = 600 mm) |              | Duplex with total visibility                   |    | FVD 30 | FVD 36 | FVD 39 |
|--|--------------|--|----|--------|--------|--------|
|  |              | h1 - Height mast lowered *                     | mm | 2392   | 2742   | 2892   |
|  |              | h3 - Lifting Height                            | mm | 3000   | 3600   | 3900   |
|  |              | h4 - Height mast extended *                    | mm | 4495   | 5095   | 5395   |
|  | Simple Reach | Pantograph reach in                            | kg | 2500   | 2500   | 2500   |
|  |              | Pantograph reach out with stabilizers          | kg | 2050   | 2050   | 2050   |
|  |              | Pantograph reach out without stabilizers       | kg | 1150   | 1100   | 1000   |
|  |              | Telescopic forks reach in                      | kg | 2500   | 2500   | 2500   |
|  |              | Telescopic Forks reach out with stabilizers    | kg | 1350   | 1300   | 1300   |
|  |              | Telescopic Forks reach out without stabilizers | kg | 1200   | 1150   | 1100   |
|  | Double Reach | Pantograph & TF reach in                       | kg | 2500   | 2500   | 2500   |
|  |              | Pantograph & TF reach out with stabilizers     | kg | 1100   | 1100   | 1100   |
|  |              | Pantograph & TF reach out without stabilizers  | kg | 550    | 550    | 550    |



Siège Social  
430 rue de l'Aubinière - 44150 Ancenis Cedex - France  
Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97  
[www.manitou.com](http://www.manitou.com)



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes